

**GMI SPMAG Flexible Magnetics**  
**.020 AND .030 Mil**  
**For Eco-Solvent and Solvent-Based Inkjet Printers**



**LEAD FREE BONDED IRON FERRITE COMPOSITE.**

**CONSTRUCTION**

Applications **Car signs, business cards, promotional products, message boards**

Face Film **4 Mil Matte White Vinyl Film**

Release Liner **None**

Outdoor Durability **Up to 3 years**

Print Methods **Silk screen, foil hot stamping, label, offset and digital printing processes**

Minimum Surface/Ambient Air Application Temperature **60° F**

Magnetization **Multi-pole magnetization. Magnetic strength at or above .020 Mil thickness is ample for car signs.**

Service Temperature Range **60° F +**

Opacity **Excellent.**

Typical Film Caliper (w/Adhesive) **4 Mil**

Product Thickness **.020 and .030 Mil**

Water Resistance **Yes.**

Shelf Life **2 Years**

Sizes	SPMAG202410N	24" X 10 FT	SMPMAG302410N	24" X 10 FT
	SPMAG202425N	24" X 25 FT	SMPMAG302425N	24" X 25 FT
	SPMAG202450N	24" X 50 FT	SMPMAG302450N	24" X 50 FT
	SPMAG203025N	30" X 25 FT	SMPMAG303025N	30" X 25 FT
	SPMAG203050N	30" X 50 FT	SMPMAG303050N	30" X 50 FT

The above information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)



If the size you require is not listed, please call GMI Inside Sales **800-388-1161**.



Visit [www.gmintl.com](http://www.gmintl.com) for downloadable ICC profiles for your specific printer and ink set.

©2008 Graphic Materials International. All rights reserved. SPMAG 040208.