

GMI SPMWG Wall Graphics

3.4 Mil Flexible White Vinyl

For Eco-Solvent, Solvent and UV-Solvent Based Inkjet Printers.



A FLEXIBLE 3.4 MIL VINYL FILM COATED WITH A SPECIALLY FORMULATED REMOVABLE ADHESIVE. ALSO AVAILABLE IN 6.0 AND 8.0 MIL. VINYL.

CONSTRUCTION

Applications	This product is intended for use as a high quality interior marking in decal applications requiring easy removal from walls with smooth surfaces. Recommended for smooth, dry, cleaned and flat surfaces.
Face Film	3.4 Mil
Adhesive Release	Removable
Liner	90 # Stayflat

PHYSICAL PROPERTIES

Interior Durability	Two (2) years interior.
Print Methods	Screen, and digital printing processes and can be top coated for improved ink adhesion for such printing methods as Offset, UV, Litho and Flexographic. Leave ¼" bleed.
Minimum Surface/Ambient Air Application Temperature	+60° F. For lower application temperature requirements, call you GMI representative about our other specialty adhesives
Service Temperature Range	65° F to 110° F
Colors	White & Clear
Typical Film Caliper (w/Adhesive)	4.1 – 4.5 Mils. With Adhesive
Product Thickness	3.4
Chemical Resistance	Good for most petroleum solvents and lower aliphatic alcohols. For ultimate solvent resistance, edge sealing is recommended.
Water Resistance	Excellent.
Adhesion	8 – 10 oz. / in.
Shelf Life	One (1) year when stored under conditions of 70° F and 50% relative humidity.
Sizes	30" X 25 YDS 30" X 50 YDS 54" x 25 YDS 54" x 50 YDS 60" x 25 YDS 60" x 50 YDS

The above information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)



If the size you require is not listed, please call GMI Inside Sales **800-388-1161**.



Visit www.gmintl.com for downloadable ICC profiles for your specific printer and ink set.

©2007 Graphic Materials International.
All rights reserved. SPMWG 052307

GMI SPMWG Wall Graphics

3.4 Mil Flexible White Vinyl

For Eco-Solvent, Solvent and UV-Solvent Based Inkjet Printers.



A FLEXIBLE 3.4 MIL VINYL FILM COATED WITH A SPECIALLY FORMULATED REMOVABLE ADHESIVE. ALSO AVAILABLE IN 6.0 AND 8.0 MIL. VINYL.

WALL GRAPHICS INSTALLATION GUIDELINES

1. Wall Graphics is intended for use as a high quality interior printable vinyl film.
2. Wall Graphics is best suited for applications requiring easy removal from such surfaces as standard painted dry walls that are smooth, clean and non-textured.
3. Vinyl must be at room temperature before printing and installation.
4. Surface must be cleaned prior to applying printed graphic. **DO NOT USE SOAP OR ANY HOUSEHOLD CLEANING AGENTS.** Surface must be completely dry before applying graphic.
5. Wall Graphic material must be allowed to dry for a minimum of 24 hours following printing before removal of liner and installation.
6. During installation a clean, dry, unused paint roller can be used to eliminate any air bubbles.

The above information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)



If the size you require is not listed, please call GMI Inside Sales **800-388-1161**.



Visit www.gmintl.com for downloadable ICC profiles for your specific printer and ink set.

©2007 Graphic Materials International.
All rights reserved. SPMWG 052307